

HSM Cutting Machines

Product Overview



HSM Rotary Trimmers

T 2606 / T 3206 / T 4606

- Cutting length 260 / 320 / 460 mm
- Cutting height up to 0.6 mm*
- Cutting capacity 6 sheets*
- Ground, self-sharpening round blade of hardened steel
- High level of operational safety thanks to completely covered cutting blade
- Cutting head easy to exchange with the rotary lock on the side of the guide axis



T 7220

- Cutting length 720 mm
- Cutting height up to 2.0 mm*
- Cutting capacity 20 sheets*
- Ground, self-sharpening round blade of hardened steel
- High level of operational safety thanks to completely covered cutting blade
- High-quality aluminium base plate with precise cm/inch scale



T 9610 / T 15007

- Cutting length 1000 / 1450 mm
- Cutting height up to 1.0 / 0.7 mm*
- Cutting capacity 10 / 7 sheets*
- Ground, self-sharpening round blade of hardened steel
- High level of operational safety thanks to completely covered cutting blade
- High-quality aluminium base plate with cm/inch scale



TA 3200

- Creative cutting for straight, wavy and perforated cutting
- For paper and other soft material
- Round blade made of hardened steel, enclosed to ensure user safety, safe and easy to change
- Storage compartment for spare blades
- Plastic base plate
- Limit stop lines for DIN formats with cm/inch



MODEL	TA 3200	T 2606	T 3206	T4606	T 7220	T 9610	T 15007
Cutting length in mm	310	260	320	460	720	1000	1450
Max. paper format	DIN A4	DIN A5/A4 landscape	DIN A4/A3 landscape	DIN A3/A2 landscape	DIN A2	DIN A1	DIN A0
Cutting height* in mm	0.6	0.6	0.6	0.6	2.0	1.0	0.7
Cutting capacity* in sheets	6 in all cutting types	6	6	6	20	10	7
Weight in kg	0.6	0,8	0,9	1.2	5.5	7.3	9.8
Dimensions (L x W x H) in mm	380 x 205 x 80	367 x 210 x 62	427 x 210 x 62	567 x 210 x 62	985 x 300 x 130	1320 x 300 x 130	1760 x 300 x 130
Base frame	-	-	-	-	•	•	•
Spare cutting head	-	•	•	•	•	•	•

* per cycle DIN A4, 70 g/m². All technical data and dimensions are approximate values. Technical and design modifications reserved.

HSM Guillotines




CM 2606 / CM 3206

- Cutting length 260 / 320 mm
- Cutting capacity up to 10 sheets*
- Cutting height 1.0 mm*
- Manual paper clamping
- Safe cutting with manual push rail - two-hand operation



CM 3815 / CM 4315

- Cutting length 380 / 430 mm
- Cutting capacity up to 15 sheets*
- Cutting height 1.3 - 1.5 mm*
- Manual paper clamping
- Cutting blade of hardened steel
- Top and bottom side limit stop
- Variable rear limit stop can be fastened to side limit stop
- Precise limit stop lines
- cm and inch scale



CM 4625



CM 3625 / CM 4625

- Cutting length 360 / 460 mm
- Cutting capacity up to 25 sheets*
- Cutting height 2.1 - 2.5 mm*
- Manual paper clamping
- High-quality ground cutting blade made of hardened steel (CM 4625: Solinger steel)
- Double protection thanks to safety grip and protective guard
- Variable rear limit stop can be fastened to side limit stop
- Precise limit stop lines
- cm and inch scale



CA 3625




CA 3625 / CA 3640 / CA 4640

- Cutting length 360 / 360 / 460 mm
- Cutting capacity up to 25 / 40 / 40 sheets*
- Cutting height 2.1 - 2.5 / 3.6 - 3.9 / 3.6 - 3.9 mm*
- Automatic paper clamping
- Double personal protection by safety grip and folding protective guard
- High-quality ground cutting blade made of hardened steel (CA 3640 and CA 4640: Solinger steel)
- Variable rear limit stop can be fastened to side limit stop
- Precise limit stop lines
- cm and inch scale

MODEL	CM 2606	CM 3206	CM 3815	CM 4315	CM 3625	CM 4625	CA 3625	CA 3640	CA 4640
Cutting length in mm	260	320	380	430	360	460	360	360	460
Max. paper format	DIN A5/A4 landscape	DIN A4/A3 landscape	DIN A4/A3 landscape	DIN A3/A2 landscape	DIN A4/A3 landscape	DIN A3/A2 landscape	DIN A4/A3 landscape	DIN A4/A3 landscape	DIN A3/A2 landscape
Cutting height* in mm	1.0	1.0	1.3 - 1.5	1.3 - 1.5	2.1 - 2.5	2.1 - 2.5	2.1 - 2.5	3.6 - 3.9	3.6 - 3.9
Cutting capacity* in sheets	10	10	15	15	25	25	25	40	40
Paper clamping	manual	manual	manual	manual	manual	manual	automatic	automatic	automatic
Weight in kg	0.8	0.9	3.6	4.4	5.4	6.6	5.6	6.2	7.6
Dimensions (L x W x H) in mm	489 x 194 x 62	549 x 194 x 62	600 x 370 x 315	650 x 435 x 335	394 x 574 x 427	394 x 687 x 447	394 x 608 x 427	394 x 608 x 427	394 x 711 x 457

*per cycle DIN A4, 70 g/m². All technical data and dimensions are approximate values. Technical and design modifications reserved.



CS 3640 / CS 4640

- Cutting length 360 / 460 mm
- Cutting capacity up to 40 sheets*
- Cutting height 3.6 - 3.9 mm*
- Automatic paper clamping
- High quality ground Solinger blade made of hardened steel
- Double personal protection thanks to safety grip and folding protective guard
- Variable rear limit stop can be fastened to side limit stop
- Variable frontal limit stop can be used on both sides, with paper supports



R 48000

- Manual paper clamping
- Safety cover and lock
- Cutting length 480 mm
- Cutting capacity up to 600 sheets*
- Indication of the cutting line
- Precise, spindle-guided rear limit stop
- Sturdy, stable steel construction
- Angle bracket for accurate stacking of the paper
- Accessory: base frame

MODEL	CS 3640	CS 4640	R 48000
Cutting length in mm	360	460	480
Max. paper format	DIN A4/A3 landscape	DIN A3/A2 landscape	DIN A3/A2 landscape
Cutting height* in mm	3.6 - 3.9	3.6 - 3.9	60
Cutting capacity* in sheets	40	40	600
Paper clamping	automatic	automatic	manual
Weight in kg	8.7	10.6	51.0
Dimensions (L x W x H) in mm	394 x 608 x 427	394 x 711 x 457	760 x 720 x 460
Base frame	-	-	•

* per cycle DIN A4, 70 g/m². All technical data and dimensions are approximate values. Technical and design modifications reserved.

	Manual paper clamping
	Automatic paper clamping
	High-quality ground Solinger cutting blade
	Cutting blade of hardened steel
	Variable frontal limit stop
	Variable rear limit stop
	Folding protective guard
	Ground, self-sharpening round blade



Simply order by fax!

Model	Quantity

Name / Company	Telephone
Number, street	Fax
City / town, postcode	e-Mail

Your HSM partner



Proudly distributed by Pitney Bowes
13 23 63
www.pitneybowes.com.au

