

DA300

Specifications

- » **Maximum speed:** Up to 4,200 items per hour - at draft mode 150 x 600 dpi, black, 3 line address, 18 characters per line, 12 point character size, DLX envelope.
- » **Print resolution:** Up to 300 x 600 dpi black.
- » **Media sizes:** Min 76mm x 127mm
Max 323mm x 393mm
Max Thickness 3mm.
- » **Effective print area:** 240mm x 380mm.
- » **Dimensions:** 370mmH, 411mmW x 551mmD.
- » **Weight:** 18.1kg.
- » **Internal fonts:** Arial, Comic Sans MS, Courier New, Georgia, Impact, Kino, MSLogo, Symbol, Tahoma, Times New Roman, Trebuchet MS, Veranda, Webdings, Wingdings and OCR-A font and a Code 39 font. All fonts are scalable from 4 to 144 point size and are only available with use of serial port.
- » **Resolution:** Three print qualities: draft (150 x 600 dpi), letter (200 x 600dpi), and executive (300 x 600dpi).
- » **Noise:** <68dBA.
- » **Supplied software:** Microsoft® Windows® Compatible Printer Drivers, Envelope Designer™ Plus.
- » **Electrical:** 240V, 50Hz.
- » **Computer requirement:** Requires an IBM® compatible PC (Pentium® III 500MHz, 500MB RAM min) running Microsoft® Windows® 2000 or XP with latest service pack.
- » **Interfaces:** Parallel & Serial
- » **Emulation:** Hewlett Packard PCL5 subset.
- » **Input stack:** 200 DLX envelopes (empty).
- » **Output stack:** 150 DLX envelopes (empty) in tray, or continuous with optional Conveyor Stacker.
- » **Optional accessories:** Conveyor stacker, heater/dryer.



DA50S/DA55S

Specifications

- » **Maximum speed:** Up to 7,700 items per hour (DA50S) or up to 7,600 items per hour (DA55S) - at draft mode 150 x 600 dpi, black, 3 line address, 18 characters per line, 12 point character size, DLX envelope.
- » **Print resolution:** Up to 600 dpi black or 300 dpi colour (colour on DA55S only).
- » **Media sizes:** Min 89mm x 114mm
Max 343mm x 324mm
Max Thickness 3.175mm.
- » **Effective print area:** 240mm x 380mm.
- » **Dimensions:** 373mmH x 412mmW x 551mmD.
- » **Weight:** 20kg.
- » **Internal memory:** 32MB, print more complex layouts, more reliability.
- » **Resolution:** Six print qualities: draft light (300 x 150 dpi), draft (150 x 600 dpi), letter light (300 x 300 dpi), letter (300 x 600 dpi), executive light (600 x 300 dpi) and executive (600 x 600 dpi).
- » **Noise:** <68dBA.
- » **Supplied software:** Microsoft® Windows® Compatible Printer Drivers, Envelope Designer™ Plus, Control panel software (monitor and control the printer from your PC. Obtain information such as piece count, current throughput and ink levels for each cartridge in the printer. Low ink management for print quality assurance).
- » **Media transport:** Auto calibrating paper sensor, DC motor and high resolution encoder.
- » **Electrical:** 240V, 50Hz.
- » **Computer requirements:** Requires an IBM® compatible PC (Pentium® III 500MHz, 500MB RAM min) running Microsoft® Windows® 2000 or XP with latest service pack.
- » **Interfaces:** USB 2.0, Ethernet.
- » **Emulation:** Hewlett Packard PCL5 subset.
- » **Input stack:** 200 DLX envelopes (empty).
- » **Output stack:** 150 DLX envelopes (empty) in tray, or continuous with optional Conveyor Stacker.
- » **Optional accessories:** Conveyor stacker, heater/dryer.

