



Relay® 2500, 3500 and 4500 Folder Inserters

The simple way to faster, more accurate mail





Sending customer communications like invoices and statements is vital to your business.

However, the complicated process of preparing mail can cause delays and errors that lead to missed deadlines and unhappy customers. The Relay folder inserter series removes the complexity of assembling mail, so you get the right message to the right customer on time, every time.

Simple meets proven.

Relay folder inserters were designed with the needs of your entire team in mind, regardless of expertise. Even if you're not technically minded, you can be running mail with minimal effort. The large colour touchscreen makes it easy to set up and select job settings. The powerful user experience is built around a tried and tested platform, giving you the confidence that your mail will be assembled quickly without interruption.



Simplicity

Designed to eliminate complexity for users at any level.



Accuracy

Eliminate costly delays due to manual errors.




Productivity

Keep your mail process moving with fast, uninterrupted performance.

Increased speed with added security

The barcode-reading technology of the Relay inserter accelerates the mailing process. Plus, it adds an extra layer of security to ensure that the right documents are sent to the right person. The advanced camera reads instructions that are contained in the barcode to automate variable-page mail. This eliminates the need to manually sort documents by page count. Your mail will be processed with superior accuracy without sacrificing speed.

Pitney Bowes document enrichment software options make adding security simple. Our SaaS or on-premise software adds barcodes directly to your existing documents without the need to involve your IT department. You can take advantage of additional value by being able to correct address data, qualify your mail for postal discounts, enhance formatting and even create and send digital versions of your documents.





The Relay folder inserters deliver simple, accurate and reliable mail processing.



Envelope feeder: Handles various letter-sized envelopes including DL and 152 x 241-mm envelopes.

User interface: Touchscreen makes it easy to set up and retrieve jobs. Start mailing in seconds.

Flexible paper handling

Choose the right fold type for your job. Folding options include C, Z, Single (half) and double fold.







Z-fold (accordion fold)



Single fold (half fold)



Double fold (parallel)

Output options

Optional vertical power stacker maintains print order and holds up to 500 finished envelopes.

Standard drop stacker shown below.



We'll help you choose the right features for your application.

		Relay 2500	Relay 3500	Relay 4500
Sheet feeder				
	Designed for lower volume applications requiring only a single document type to be folded and inserted.	\	_	_
	Allows you to fold and insert two types of documents. Double your capacity by linking the feeders for total capacity of 650 total sheets.	_	✓	✓
		Relay 2500	Relay 3500	Relay 4500
Envelope feeder		Relay 2500	Relay 3500	Relay 4500
Envelope feeder	100-envelope capacity tray can handle variety of letter envelope sizes.	Relay 2500	Relay 3500	Relay 4500

A user experience designed with you in mind.





Responsive touchscreen



Automated adjustments



Easy-to-follow guides



Quick job selection

Specifications for Relay® 2500, 3500 and 4500







System	Relay 2500	Relay 3500	Relay 4500
Cycle speed	2,500 per hour	3,000 per hour	3,500 per hour
Monthly capacity	Up to 10,000/month	Up to 20,000/month	Up to 42,500/month
Feeder Configuration	1 Sheet Fdr, 1 large insert fdr, outer envelope fdr	2 Sht Fdr, 1 large insert fdr, outer envelope fdr	2 Sheet fdr, large insert fdr, high-capacity envelope fdr
Fold options	C, Z, Half (V), Double	C, Z, Half (V), Double	C, Z, Half (V), Double
Integrity Options	OMR, 2D (C Fold Only)	OMR, 2D (All Folds)	OMR, 2D (All Folds)
Sheet feeder capacity	325	325 each	325 each
Insert feeder capacity	300	300	300
Envelope feeder capacity	100	100	300
Programmable jobs	20	20	20

Physical specifications						
Tabletop dimensions	711 mm L x 533 mm W x 635 mm H	711 mm L x 533 mm W x 635 mm H	991 mm L x 533 mm W x 635 mm H			
Full installed dimensions	1067 mm L x 533 mm W x 635 mm H	1067 mm L x 533 mm W x 635 mm H	1067 mm L x 533 mm W x 635 mm H			
Weight	63 kg	66 kg	72 kg			

^{*}Based on 75 gsm



Australia

Level 1, 68 Waterloo Road Macquarie Park NSW 2113 13 23 63 pitneybowes.com/au

New Zealand Unit B1 & B4 72 Apollo Drive Rosedale Auckland 0632 0800 748 639 pitneybowes.com/nz

For more information, call or visit us online.