

DM125i™ Digital Mailing System

Designed with flexibility in mind, the DM125i™, powered by Pitney Bowes' IntelliLink™ technology represents the ultimate answer to the mailing needs of busy businesses. The latest digital technology makes processing mail quiet and efficient - the perfect office companion.



DM125i™ Digital Mailing System

★ Future-proof mailing

IntelliLink™ connects Pitney Bowes' DM125i™ to a secure server, via the Internet, enabling services such as postal tariff changes, software updates and advertising slogans to be downloaded quickly and effortlessly.

» Correct value postage – every letter, every time

The DM125i™ incorporates a 2.5kg integral weighing platform, freeing up desk space and guaranteeing that each letter or package bears the correct postage value.

★ Fast, accurate postage re-crediting

Replenish your meter 24-hours a day with simple one-touch refills via **POSTAGE BY PHONE** – quick, secure and hassle-free. Get up to 55 days free credit with PurchasePower post now, pay later facility.

» Easy to use

All controls are fully integrated on one clear control panel with user-friendly instructions to guide the operator through each stage of processing mail.

» Streamlined processing

Efficiently frank and seal mail pieces up to 9.5mm thick, whilst larger mail is quickly processed with self adhesive tape strips. Mailing couldn't be simpler with up to 5 presets for your most commonly used jobs.

» Monitor postal spend

Control postage costs with tracking and reporting for up to 25 named departmental or client accounts.

» Strengthen your brand

Enhance and build your corporate identity by transforming standard envelopes into eye-catching branded mail pieces.

★ Track incoming mail

Date and time stamping incoming post ensures mail is handled efficiently.

DM125i™ Specifications



» Physical dimensions

Length	345mm
Depth	400mm
Height	230mm
Weight	6.8 kg approximate

» Speed

Up to 30 letters per minute

» Material sizes

Minimum material size	76mm x 127mm
Maximum material size	330mm x 381mm
Material thickness	9.5mm (max) to 0.18mm (min)
Envelope flap depth for sealing	76 (max) to 22mm (min)

» Standard operating features

Date and time stamping
Slogan and town circle download (by modem)
2.5kg integrated weighing platform
Auto-dating
Water level indicator
Seal only/no seal modes
Low postage warning
High value protection
Original value resetting
Low ink warning
Password security
PC interface
5 Job Presets
25 Accounts

» Electrical

100-240 V, 50/60 Hz, 3A

» Noise

55dB

» Connectivity requirements

Connects to a standard analog phone line

Pitney Bowes

Elizabeth Way, Harlow, Essex CM19 5BD
Tel 08705 252525 • Fax 08705 449450
www.pitneybowes.co.uk

© 2004 Pitney Bowes. All rights reserved.

Specifications are subject to change without notice. Performance may vary depending on exact job configuration and environmental conditions.