



Mailing  
Printing

RISO ComColor® GD Series Printers

# Optional accessories

Flexibility designed to meet your high capacity needs



## High Capacity Feeder

The High Capacity Feeder allows 4,000 sheets of paper to be loaded for continuous feeding. Maximize the benefits of high-speed printing with uninterrupted, high-volume print runs without pausing to reload paper.

<b>Type</b>	External unit
<b>Paper size</b>	Maximum: 13 3/8" × 18 5/16" (340 mm × 465 mm) Minimum: 3 9/16" × 5 27/32" (90 mm × 148 mm)
<b>Paper type and weight</b>	12-lb bond to 56-lb bond (46 gsm to 210 gsm ) (plain paper, recycled paper)
<b>Tray capacity</b>	Height up to 17 11/32" (440mm)
<b>Power source</b>	AC 100 V - 240 V, 1.0 A - 0.5 A 50 Hz - 60 Hz
<b>Power consumption</b>	Max. 100 W; Ready <sup>1</sup> : 30 W or less; Sleep <sup>2</sup> : 30 W or less; Stand-by: 0.5 W or less
<b>Operating noise</b>	Max. 68 db (A) A4-long-edge feed (Simplex) at the maximum print speed
<b>Dimensions (W x D x H)</b>	31 1/8" × 24 13/16" × 29 5/32" (790 mm × 630 mm × 740 mm)
<b>Required space with printer (W x D x H)</b>	61 5/8" × 48 13/16" × 45 11/16" (1,565 mm × 1,240 mm × 1,160 mm)
<b>Weight</b>	Approx. 152 lb. (69 kg.)
<b>Safety information</b>	IEC60950-1 compliant, Indoor, pollution degree 2 <sup>3</sup> , At altitudes of 6,562 feet (2,000 m) or lower.



<sup>1</sup>Without printing operation. <sup>2</sup>When setting [Power Consumption (in Sleep)] to [Low].

<sup>3</sup>The pollution degree of the usage environment due to dirt and dust in the air. Degree "2" corresponds to a general indoor environment.

## High Capacity Stacker

The High Capacity Stacker allows stacking of larger output volumes with reduced user intervention. Convenient removal and transport of the printed output is possible using the optional High Capacity Stacker Cart.

<b>Type</b>	External unit
<b>Finishing functions</b>	Collating, offset stacking
<b>Paper size</b>	Maximum: 13 3/8" × 18 1/8" (340 mm × 460 mm) Minimum: 3 9/16" × 5 27/32" (90 mm × 148 mm) Offset: 3 9/16" × 7 3/16" - 13 3/8" × 17" (90 mm × 182 mm - 340 mm × 432 mm) (Envelopes are not acceptable.)
<b>Paper type and weight</b>	12-lb bond to 56-lb bond (46 gsm to 210 gsm) (plain paper, recycled paper)
<b>Tray capacity</b>	Collating: Height up to 17 11/32" (440mm) <sup>1</sup> Offset: Height up to 15 15/16" (405mm) <sup>2</sup>
<b>Power source</b>	AC 100 V - 240 V, 1.4 A - 0.7 A, 50 Hz - 60 Hz
<b>Power consumption</b>	Max. 140 W; Ready <sup>3</sup> : 30 W or less; Sleep <sup>4</sup> : 30 W or less; Stand-by: 0.5 W or less
<b>Operating noise</b>	68 dB (A) or less A4-long-edge feed (Simplex/duplex) at the maximum print speed
<b>Dimensions (W x D x H)</b>	39 3/8" × 27 9/16" × 37 13/16" (1,000 mm × 700 mm × 960 mm)
<b>Required space with printer (W x D x H)</b>	87 1/32" x 51 25/32" x 45 11/16" (2,210 mm × 1,315 mm × 1,160 mm)
<b>Weight</b>	Approx. 298 lb. (135 kg)
<b>Safety information</b>	IEC60950-1 compliant, Indoor, pollution degree 2 <sup>5</sup> , At altitudes of 6,562 feet (2,000 m) or lower.

<sup>1</sup>Height up to 4.3" (110m) for A5, non-regular size paper. <sup>2</sup> Not applicable to A5, non-regular size paper, etc.

<sup>3</sup> Without printing operation. <sup>4</sup> When setting [Power Consumption (in Sleep)] to [Low]. <sup>5</sup> The pollution degree of the usage environment due to dirt and dust in the air. Degree "2" corresponds to a general indoor environment.



Cart not included with High Capacity Stacker.

## Face Down Finisher G10

The compact finisher is built exclusively for offset stacking and stapling finished prints.

<b>Type</b>	External unit
<b>Finishing functions</b>	Offset stacking, staple
<b>Paper size</b>	Without offset Maximum: 13 3/8" × 21 5/8" (340 mm × 550 mm) Minimum: 3 9/16" × 5 27/32" (90 mm × 148 mm)  Offset output Regular-sized paper width: 7 3/16" × 10 1/8" - 11 11/16" × 17" (182 mm × 257 mm - 297 mm × 431.8 mm) Irregular-sized paper width: 5 3/16" × 5 27/32" - 12" × 21 5/8" (131 mm × 148 mm - 305 mm × 550 mm)
<b>Paper weight</b>	12-lb bond to 56-lb bond (46 gsm to 210 gsm)
<b>Tray capacity</b>	Height up to 4 1/4" (108 mm)
<b>Maximum number of staples</b>	50 sheets*: Letter, letter long-edge feed, A4, A4 long-edge feed, B5(JIS), B5(JIS) long-edge feed 25 sheets*: Ledger, legal, A3, B4(JIS), foolscap *When using plain paper and recycled paper (23-lb bond (85 gsm))
<b>Paper size for staple</b>	Letter, letter long-edge feed, ledger, legal, foolscap, A3, B4(JIS), A4, A4 long-edge feed, B5(JIS), B5(JIS) long-edge feed
<b>Paper weight for staple</b>	14-lb bond to 56-lb bond (52 gsm to 210 gsm) (plain paper, recycled paper)
<b>Staple position</b>	1 at front side (angle stapling) 1 at rear side (angle stapling) 2 at center (parallel stapling)
<b>Power source</b>	AC 100 V - 240 V, 1.2 A - 0.6 A, 50 Hz - 60 Hz
<b>Power consumption</b>	Max. 110 W
<b>Dimensions (W × D × H)</b>	29 15/16" × 26 25/32" × 23 1/32" (760 mm × 680 mm × 585 mm)
<b>Required space with printer (W × D × H)</b>	56 11/16" × 48 13/16" × 52 31/32" (1,440 mm × 1,240 mm × 1,345 mm)
<b>Weight</b>	Approx. 66 lb (30 kg)
<b>Safety information</b>	IEC60950-1 compliant, Indoor, pollution degree 2 <sup>1</sup> , At altitudes of 6,562 feet (2,000 m) or lower.



<sup>1</sup>The pollution degree of the usage environment due to dirt and dust in the air. Degree "2" corresponds to a general indoor environment.

## Multifunction Finisher FG10

A versatile finisher that saves time by automatically stapling, punching holes, and folding.

Type	External unit	
Tray type	Top tray	Collating, stacking
	Stacking tray	Collating, offset stacking
	Booklet tray	Booklet, paper folding
Paper size	Top tray <sup>*1</sup>	Maximum: 13" × 19 3/16" (330 mm × 488 mm) Minimum: 3 15/16" × 5 27/32" (100 mm × 148 mm)
	Stacking tray <sup>*1</sup>	Maximum: 13" × 19 3/16" (330 mm × 488 mm) Minimum: 7 3/16" × 7 3/16" (182mm × 182mm)
	Booklet tray <sup>*1</sup>	Maximum: 13" × 18" (330 mm × 457 mm) Minimum: 8 1/4" × 11" (210 mm × 280 mm)
Paper weight	Top tray	14-lb bond to 56-lb bond (52 gsm to 210 gsm)
	Stacking tray	14-lb bond to 56-lb bond (52 gsm to 210 gsm)
	Booklet tray	16-lb bond to 24-lb bond (60 gsm to 90 gsm) (cover: 16-lb bond to 56-lb bond (60 gsm to 210 gsm))
Tray capacity	Top tray	Height up to 1 15/16" (50 mm)
	Stacking tray	Height up to 7 7/8" (200 mm)
	Booklet tray	Height up to 1 15/16" (50 mm)
Stapling	Maximum number of staples <sup>*2</sup>	100 sheets: Letter, letter long-edge feed, A4, A4 long-edge feed, B5(JIS) long-edge feed 65 sheets: Legal, ledger, foolscap, A3, B4(JIS)
	Paper Size	Maximum: 11 11/16" × 17" (297 mm × 432 mm) Minimum: 8" × 7 3/16" (203 mm × 182 mm)
	Staple position	1 at front side (angle stapling) 1 at rear side (angle stapling <sup>*3</sup> , parallel stapling) 2 at center (parallel stapling)
Punching	Number of punches	2 holes, 3 holes 2 holes, 4 holes
	Paper size	2 holes: Letter, letter long-edge feed, legal, ledger, A3, B4(JIS), A4 long-edge feed, A4, B5(JIS) long-edge feed 3 holes: Letter, long-edge feed, ledger, A3, B4(JIS), A4 long-edge feed, B5(JIS) long-edge feed 4 holes: Letter, long-edge feed, ledger, A3, A4 long-edge feed
	Paper weight	14-lb bond to 53-lb bond (52 gsm to 200 gsm)
Creating a booklet (Center margin/2-fold)	Maximum number of sheets <sup>*2*4</sup>	Center margin: 60 pages (15 sheets) 2-fold: 20 pages (5 sheets)
Power source	AC 100 V - 240 V, 50 Hz - 60 Hz, 2.0 A - 1.0 A	
Power consumption	Max. 175 W	
Operating noise	68 dB (A) or less	
Dimensions (W x D x H)	44 3/32" × 30 1/8" × 44 1/2" (1,120 mm × 765 mm × 1,130 mm)	
Required space with printer (W x D x H)	With folder unit	99 7/32" × 52 3/4" × 45 11/16" (2,520 mm × 1,340 mm × 1,160 mm)
	Without folder unit	91 5/32" × 50 13/32" × 45 11/16" (2,315 mm × 1,280 mm × 1,160 mm)
Weight	Approx. 289 lb (131 kg)	
Safety information	IEC60950-1 compliant, Indoor, pollution degree 2 <sup>*5</sup> , At altitudes of 6,562 feet (2,000 m) or lower.	



<sup>\*1</sup>When color printing on paper that is longer than 17" (432 mm), the image printed beyond 17" (432 mm) may be distorted.

<sup>\*2</sup>When using plain paper or recycled paper (23-lb bond or 85 gsm)

<sup>\*3</sup>Rear-side angle stapling is only available for A4 long-edge feed and A3.

<sup>\*4</sup>Includes an added cover.

<sup>\*5</sup>The pollution degree of the usage environment due to dirt and dust in the air. Degree "2" corresponds to a general indoor environment.

## Scanner HS7000

A one-pass duplex scanner improves scanning or copying, boasting a simplex/ duplex scanning speed of 100 pages per minute and copying speed of 70 pages per minute. User name is automatically added to the document name, and each page of scanned data can be saved as individual PDFs. Features like ZIP compression and saving in PDF/A format are also available.

<b>Type</b>	Flat bed scanner with Automatic Document Feeder (ADF)	
<b>Scanning modes</b>	Copy mode: Color, Monochrome, Auto, Cyan, Magenta Scan mode: Color, Monochrome, Auto, Grayscale	
<b>Scanning resolution</b>	600 dpi, 400 dpi, 300 dpi, or 200 dpi	
<b>Maximum scanning area</b>	11 15/16" × 17" (303 mm × 432 mm) (when using platen glass); 11 5/8" × 16 15/16" (295 mm × 430 mm) (when using ADF)	
<b>Copy</b>	Writing resolution	Standard: 300 dpi × 300 dpi Fine: 300 dpi × 600 dpi
	Copy paper size	Maximum: 11 15/16" × 17" (303 mm × 432 mm)
	First copy time	Monochrome/Color: 7 sec. or less (when copying A4/Letter long-edge feed orientation using Color Priority Mode)
	Copying speed	Simplex copying (A4/Letter long-edge feed, using ADF): 70 ppm or higher Duplex copying (A4/Letter long-edge feed, using ADF): 70 ppm or higher
	Reproduction size	50% to 200% (Copy mode) 50% to 200% (Scanner mode, resolution: 200/300 dpi) only 100% (Scanner mode, resolution: 400/600 dpi)
<b>Auto Document Feeder</b>	Type	Original source displacement (capable of scanning both sides of a document by simultaneous duplex scanning)
	Original size	Maximum: 11 11/16" × 17" (297 mm × 432 mm) Minimum: 3 15/16" × 5 27/32" (100 mm × 148 mm)
	Paper weight	14-lb bond to 34-lb bond (52 gsm to 128 gsm)
	Original capacity	Max. 200 sheets: 21-lb bond (80 gsm) Height up to 1" (25 mm)
<b>Scan</b>	Scanning gray levels	10-bit input and 8-bit output for each RGB color
	Scanning speed	Monochrome/Color: 100 ppm. *RISO KAGAKU standard original (A4/Letter long-edge feed), 300 dpi, JPEG, PDF, when stored to main unit hard drive
	Network interface <sup>1</sup>	Ethernet 1000BASE-T/100BASE-TX/10BASE-T
	Data-saving method <sup>1</sup>	Save to main unit hard drive, server, or USB flash drive, or send by e-mail
	Data-saving format <sup>1</sup>	Monochrome: TIFF, PDF, PDF/A Grayscale/Full Color: TIFF, JPEG, PDF, PDF/A
<b>Power source</b>	AC 100 V - 240 V, 1.2 A - 0.6 A, 50 Hz - 60 Hz	
<b>Power consumption</b>	Max. 100 W	
<b>Dimensions (W × D × H)</b>	25 3/16" × 22 1/16" × 10 1/32" (640 mm × 560 mm × 255 mm)	
<b>Required space with printer (W × D × H)</b>	48 5/8" × 52 31/32" × 64 3/8" (1,235 mm × 1,345 mm × 1,635 mm)	
<b>Weight</b>	Approx. 55 lb (25 kg)	
<b>Safety information</b>	IEC60950-1 compliant, Indoor, pollution degree 2 <sup>2</sup> , At altitudes of 6,562 feet (2,000 m) or lower.	



<sup>1</sup>Via the internal host controller.

<sup>2</sup>The pollution degree of the usage environment due to dirt and dust in the air. Degree "2" corresponds to a general indoor environment.

## Auto-Control Stacking Tray II

The paper guides automatically open to the correct width to match the paper in use.

<b>Paper size</b>	Maximum: 12 9/16" × 17" (320 mm × 432 mm) Minimum: 3 15/16" × 5 13/16" (90 mm × 148 mm)
<b>Tray capacity*</b>	1,000 sheets

\* When using plain paper or recycled paper (23-lb bond or 85 gsm)



## Wide Stacking Tray

Wider paper can be printed and stacked in a wider tray to match the paper in use.

<b>Paper size</b>	Maximum: 13 3/8" × 21 5/8" (340 mm × 550 mm) Minimum: 3 15/16" × 5 13/16" (90 mm × 148 mm)
<b>Tray capacity*</b>	1,000 sheets

\* When using plain paper or recycled paper (23-lb bond or 85 gsm)



**United States**  
3001 Summer Street  
Stamford, CT 06926-0700

For more information,  
visit us online: [pitneybowes.com/us/risoGD](http://pitneybowes.com/us/risoGD)