



Mailing

Printing



## RISO ComColor® GD Inkjet Printer Specifications

### GD7330

Print type		Line-type inkjet system
Ink type		Oil-based pigment ink (Cyan, Magenta, Yellow, Black, Gray)
Print resolution	Standard/High chromogenic	Black 600 dpi (main scanning direction) × 600 dpi (sub-scanning direction) Cyan, Magenta, Yellow, Gray 300 dpi (main scanning direction) × 300 dpi (sub-scanning direction)
	Fine	Black 600 dpi (main scanning direction) × 600 dpi (sub-scanning direction) Cyan, Magenta, Yellow, Gray 300 dpi (main scanning direction) × 600 dpi (sub-scanning direction)
Number of gray levels		Black 4 gray levels. Cyan, Magenta, Yellow, Gray 12 gray levels
Print resolution	Standard/High chromogenic	Black 600 dpi × 600 dpi. Cyan, Magenta, Yellow, Gray 300 dpi × 300 dpi
	Fine	Black 600 dpi × 600 dpi. Cyan, Magenta, Yellow, Gray 300 dpi × 600 dpi
	Line smoothing	600 dpi × 600 dpi
Warm-up time		2 minutes 30 seconds or less (at room temperature of 23 °C (73.4 °F))
First print time <sup>1</sup>		5 seconds or less (A4 long-edge feed)
First copy time <sup>1</sup>		7 seconds or less (A4 long-edge feed)
Continuous print speed <sup>2,3</sup>	A4 long-edge feed	Simplex 130 ppm, Duplex 65 sheets/minute (130 ppm)
	Letter long-edge feed	Simplex 130 ppm, Duplex 65 sheets/minute (130 ppm)
	A4 short-edge feed	Simplex 104 ppm, Duplex 52 sheets/minute (104 ppm)
	Letter short-edge feed	Simplex 104 ppm, Duplex 52 sheets/minute (104 ppm)
	B4 (JIS) short-edge feed	Simplex 88 ppm, Duplex 42 sheets/minute (84 ppm)
	Legal short-edge feed	Simplex 90 ppm, Duplex 42 sheets/minute (84 ppm)
	A3 short-edge feed	Simplex 78 ppm, Duplex 38 sheets/minute (76 ppm)
Paper size	Standard tray	Maximum 340 mm × 550 mm (13 3/8" × 21 5/8"). Minimum 90 mm × 148 mm (3 9/16" × 5 27/32")
	Feed tray	Maximum 297 mm × 432 mm (11 11/16" × 17"). Minimum 182 mm × 182 mm (7 3/16" × 7 3/16")
Printable area		314 mm × 548 mm (12 3/8" × 21 19/32")
Guaranteed print area <sup>4</sup>		Standard margin width of 3 mm (1/8"). Maximum margin width of 1 mm (3/64")
Paper weight	Standard tray	46 gsm to 210 gsm (12-lb bond to 56-lb bond)
	Feed tray	52 gsm to 104 gsm (14-lb bond to 28-lb bond)
Paper tray capacity	Standard tray	Height up to 110 mm (4 5/16")
	Feed tray	Height up to 56 mm (2 3/16") (×3 trays)
Output tray capacity		Height up to 60 mm (2 3/8")
PDL (Page Description Language)		RISORINC/C IV
Supported protocols		TCP/IP, HTTP, HTTPS (TLS), DHCP, ftp, lpr, IPP, SNMP, Port9100 (RAW port), IPv4, IPv6, IPsec
Supported operating systems	Standard	Microsoft® Windows Vista® (32-bit/64-bit), Windows® 7 (32-bit/64-bit), Windows® 8.1 (32-bit/64-bit), Windows® 10 (32-bit/64-bit), Windows Server® 2008 (32-bit/64-bit), Windows Server® 2008 R2 (64-bit), Windows Server® 2012 (64-bit), Windows Server® 2012 R2 (64-bit)
Network interface		Ethernet 1000BASE-T, 100BASE-TX, 10BASE-T (2ch)
Memory capacity		4 GB
Hard Disk <sup>5</sup>	Capacity	500 GB
	Available space	Approximately 430 GB
Operating system		Linux
Power source		AC 100 V-240 V, 12.0 A-6.0 A, 50 Hz-60 Hz
Power consumption		Maximum: 1,200 W, Ready <sup>6</sup> : 150 W or less, Sleep <sup>7</sup> : 4 W or less, Stand-by 0.5: W or less
Operating noise		Maximum 66 dB (A) A4 long-edge feed (Simplex) at the maximum print speed
Operating environment		Temperature 15 °C to 30 °C (59 °F to 86 °F). Humidity 40% to 70% RH (non-condensing)
Dimensions (W × D × H)		In use: 1,220 mm × 725 mm × 1,160 mm (48 1/32" × 28 17/32" × 45 21/32") With cover and tray closed: 1,160 mm × 705 mm × 1,015 mm (45 21/32" × 27 3/4" × 39 15/16")
Required space (W × D × H) <sup>8</sup>		1,220 mm × 1,240 mm × 1,160 mm (48 1/32" × 48 13/16" × 45 21/32")
Weight		Approximately 175 kg (386 lb)
Safety information		IEC60950-1 compliant, Indoor, pollution degree 2 <sup>9</sup> , At altitudes of 2,000 m or lower

For more information, visit us online: [pitneybowes.com/us/risogd](http://pitneybowes.com/us/risogd)

## GD9630

Print type		Line-type inkjet system
Ink type		Oil-based pigment ink (Cyan, Magenta, Yellow, Black, Gray)
Print resolution	Standard/High chromogenic	Black 600 dpi (main scanning direction) × 600 dpi (sub-scanning direction) Cyan, Magenta, Yellow, Gray 300 dpi (main scanning direction) × 300 dpi (sub-scanning direction)
	Fine	Black 600 dpi (main scanning direction) × 600 dpi (sub-scanning direction) Cyan, Magenta, Yellow, Gray 300 dpi (main scanning direction) × 600 dpi (sub-scanning direction)
Number of gray levels		Black 4 gray levels. Cyan, Magenta, Yellow, Gray 12 gray levels
Print resolution	Standard/High chromogenic	Black 600 dpi × 600 dpi. Cyan, Magenta, Yellow, Gray 300 dpi × 300 dpi
	Fine	Black 600 dpi × 600 dpi. Cyan, Magenta, Yellow, Gray 300 dpi × 600 dpi
	Line smoothing	600 dpi × 600 dpi
Warm-up time		2 minutes, 30 seconds or less (at room temperature of 23 °C (73.4 °F))
First print time <sup>11</sup>		5 seconds or less (A4 long-edge feed)
First copy time <sup>11</sup>		7 seconds or less (A4 long-edge feed)
Continuous print speed <sup>2,3</sup>	A4 long-edge feed	Simplex 160 ppm, Duplex 80 sheets/minute (160 ppm)
	Letter long-edge feed	Simplex 160 ppm, Duplex 80 sheets/minute (160 ppm)
	A4 short-edge feed	Simplex 120 ppm, Duplex 60 sheets/minute (120 ppm)
	Letter short-edge feed	Simplex 120 ppm, Duplex 60 sheets/minute (120 ppm)
	B4 (JIS) short-edge feed	Simplex 102 ppm, Duplex 44 sheets/minute (88 ppm)
	Legal short-edge feed	Simplex 104 ppm, Duplex 44 sheets/minute (88 ppm)
	A3 short-edge feed	Simplex 88 ppm, Duplex 42 sheets/minute (84 ppm)
Paper size	Standard tray	Maximum 340 mm × 550 mm (13 3/8" × 21 5/8"). Minimum 90 mm × 148 mm (3 9/16" × 5 27/32")
	Feed tray	Maximum 297 mm × 432 mm (11 11/16" × 17"). Minimum 182 mm × 182 mm (7 3/16" × 7 3/16")
Printable area		314 mm × 548 mm (12 3/8" × 21 9/32")
Guaranteed print area <sup>4</sup>		Standard margin width of 3 mm (1/8"). Maximum margin width of 1 mm (3/64")
Paper weight	Standard tray	46 gsm to 210 gsm (12-lb bond to 56-lb bond)
	Feed tray	52 gsm to 104 gsm (14-lb bond to 28-lb bond)
Paper tray capacity	Standard tray	Height up to 110 mm (4 5/16")
	Feed tray	Height up to 56 mm (2 3/16") (×3 trays)
Output tray capacity		Height up to 60 mm (2 3/8")
PDL (Page Description Language)		RISORINC/C IV
Supported protocols		TCP/IP, HTTP, HTTPS (TLS), DHCP, ftp, lpr, IPP, SNMP, Port9100 (RAW port), IPv4, IPv6, IPSec
Supported operating systems	Standard	Microsoft® Windows Vista® (32-bit/64-bit), Windows® 7 (32-bit/64-bit), Windows® 8.1 (32-bit/64-bit), Windows® 10 (32-bit/64-bit), Windows Server® 2008 (32-bit/64-bit), Windows Server® 2008 R2 (64-bit), Windows Server® 2012 (64-bit), Windows Server® 2012 R2 (64-bit).
Network interface		Ethernet 1000BASE-T, 100BASE-TX, 10BASE-T (2ch)
Memory capacity		4 GB
Hard Disk <sup>5</sup>	Capacity	500 GB
	Available space	Approximately 430 GB
Operating system		Linux
Power source		AC 100 V – 240 V, 12.0 A – 6.0 A, 50 Hz – 60 Hz
Power consumption		Maximum: 1,200 W, Ready <sup>6</sup> : 150 W or less, Sleep <sup>7</sup> : 4 W or less, Stand-by 0.5: W or less.
Operating noise		Maximum 66 dB (A) A4 long-edge feed (Simplex) at the maximum print speed
Operating environment		Temperature 15 °C to 30 °C (59 °F to 86 °F). Humidity 40% to 70% RH (non-condensing)
Dimensions (W × D × H)		In use: 1,220 mm × 725 mm × 1,160 mm (48 1/32" × 28 17/32" × 45 21/32") With cover and tray closed: 1,160 mm × 705 mm × 1,015 mm (45 21/32" × 27 3/4" × 39 15/16")
Required space (W × D × H) <sup>8</sup>		1,220 mm × 1,240 mm × 1,160 mm (48 1/32" × 48 13/16" × 45 21/32")
Weight		Approximately 175 kg (386 lb)
Safety information		IEC60950-1 compliant, Indoor, pollution degree 2 <sup>9</sup> , At altitudes of 2,000 m or lower

<sup>11</sup> Within 10 minutes after the last print job.

<sup>12</sup> When using plain paper and recycled paper (85 gsm (23-lb bond)), and standard density setting. Chart used print measurement pattern [Color measurement sample 2 (JEITA standard pattern J6)].

<sup>13</sup> The continuous print speed varies depending on the type of optional output equipment connected.

<sup>14</sup> The margin when printing envelopes is 10 mm (3/8"). The guaranteed area when printing images is the area enclosed within 3 mm (1/8") of the edges of the paper.

<sup>15</sup> One gigabyte (GB) is calculated as 1 billion bytes.

<sup>16</sup> Without printing and temperature adjustment operation.

<sup>17</sup> When setting [Power Consumption (in Sleep)] to [Low]

<sup>18</sup> With the front cover open and the operation panel in the upright position

<sup>19</sup> The pollution degree of the usage environment due to dirt and dust in the air. Degree "2" corresponds to a general indoor environment.



United States  
3001 Summer Street  
Stamford, CT 06926-0700