

MapInfo RouteFinder

2015

pitney bowes

Product Guide




Information in this document is subject to change without notice and does not represent a commitment on the part of the vendor or its representatives. No part of this document may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying without the written permission of Pitney Bowes Inc.

© 2015 Pitney Bowes. All rights reserved. MapInfo, MapInfo Professional, StreetPro and MapInfo RouteFinder are trademarks of Pitney Bowes and/or its affiliates.

Products named herein may be trademarks of their respective manufacturers and are hereby recognised. Trademarked names are used editorially, to the benefit of the trademark owner, with no intent to infringe on the trademark.

Adobe Acrobat® is a registered trademark of Adobe Systems Incorporated in the United States.

Copyright and Licence



StreetPro © 2015 Pitney Bowes Pty Ltd. All rights reserved.

<http://www.pitneybowes.com.au/software>

Pitney Bowes Pty Ltd is the largest distributor of digital spatial data products in Australia. By nurturing solid relationships with PSMA Australia, State/Territory jurisdictions and its significant customer base, Pitney Bowes Pty Ltd is able to offer cost effective digital data products that meet the current and future needs of the Australian marketplace. This quality spatial data product has been compiled with the assistance of content suppliers like those referenced below.



© 2006-2015 TomTom. All rights reserved.

<http://www.tomtom.com>

This material is proprietary and the subject of copyright protection, database right protection and other intellectual property rights owned by TomTom or its suppliers. The use of this material is subject to the terms of a license agreement. Any unauthorized copying or disclosure of this material will lead to criminal and civil liabilities.

The above providers do not warrant that the data does not contain errors, and shall be in no way liable for any loss, damage or injury suffered by the user or any other person or corporation consequent upon the existence of any errors in the data.

Other Data Providers



Transport and Topography and G-NAF® © 2015 PSMA Australia Ptd Ltd. All rights reserved.

<http://www.pasma.com.au>

PSMA Australia's Transport and Topography data covers the whole of Australia and consists of three themes: Transport, Hydrology and Greenspace. It is underpinned by a road centerline layer of over two million kilo metres of roads, together with more than 30 feature types within the Transport, Hydrology and Greenspace themes.

G-NAF® (Geocoded National Address File) is Australia's first authoritative geocoded address index for the whole country, listing all valid physical addresses in Australia. Data used to build G-NAF® comes from contributors that include the Australian Electoral Commission, Australia Post, state, territory and Australian Government mapping agencies and land registries. PSMA Australia does not warrant the accuracy or completeness of information in this publication and any person using or relying upon such information does so on the basis that PSMA Australia shall bear no responsibility or liability whatsoever for any errors, faults, defects or omissions in the information.



© 2015 MapKing. All rights reserved.

<http://www.mapking.com>

The StreetPro China product has been compiled under license using data from MapKing. All rights reserved. MapKing does not warrant that the data does not contain errors and shall be in no way liable for any loss, damage or injury suffered by the user or any other person or corporation consequent upon the existence of any errors in the data.



© PT Duta Astakona Girinda

<http://www.dag.co.id>

PT Duta Astakona Girinda does not warrant the accuracy or completeness of information in this publication or the data in the StreetPro Indonesia product, and any person using or relying upon such information does so on the basis that PT Duta Astakona Girinda shall bear no responsibility or liability whatsoever for any errors, faults, defects or omissions in the information or the data.



© 2015 INCREMENT P CORPORATION. All rights reserved.

<http://www.incrementp.co.jp/>



© 2015. Japan Digital Road Map Association

<http://www.drm.jp/>

This map uses the publication's national digital road map databases Digital Road Map Association Foundation. (Approved under section 44 of the Act by using survey results <90-063>)



©Critchlow™
© New Zealand Crown copyright

<http://www.critchlow.co.nz>

NZ address, street, suburb, locality and postcode boundary data is supplied by Critchlow™ and includes data licensed by Land Information New Zealand ("LINZ") under LINZ license HH/097637/2. New Zealand Crown copyright exists in all LINZ licensed data. Critchlow™ also reserves copyright in the value-add component of the data. Critchlow™ does not warrant the accuracy or completeness of information in this publication or the data in this product, and any person using or relying upon such information does so on the basis that Critchlow™ shall bear no responsibility or liability whatsoever for any errors, faults, defects or omissions in the information or data.



Ordnance Survey © Crown Copyright 2015. All right reserved.

<http://www.ordnancesurvey.co.uk/>

Licence number 100020348.
Contains National Statistics data © Crown Copyright and database right 2015.

Further Information

Pitney Bowes Pty Ltd, Asia-Pac Headquarters
Suite 1, Level 1, 68 Waterloo Road
Macquarie Park
NSW 2113 Australia
Phone: +61.2.9437.6255
Fax: +61.2.9439.1773
Email: software.support@pb.com
Web: <http://www.pitneybowes.com.au/software>

Pitney Bowes UK and EMEA Headquarters
The Smith Centre, The Fairmile
Henley-on-Thames
Oxfordshire
RG9 6AB
United Kingdom
Phone: +44 (0) 800 840 0001
E-mail: software.support@pb.com
Web: <http://www.pitneybowes.co.uk/software>

Pitney Bowes Corporate Headquarters
One Global View
Troy, New York 12180, United States
Voice: (518) 285-6000
Fax: (518) 285-6070
Sales Info Hotline: (800) 327-8627
Government Sales Hotline: (800) 619-2333
Technical Support Hotline: (518) 285-7283
Technical Support Fax: (518) 285-6080
Email: software.support@pb.com
Web: <http://www.pitneybowes.com/us>

July 2015

Table of Contents

Chapter 1: Introduction	6
Overview	7
Contacting Technical Support	7
Data Vintage	7
Chapter 2: Getting Started	8
File Names	9
Links	9
Installing RouteFinder Data	10
Chapter 3: Database Description	11
Spatial Referencing	12
Display Characteristics and Table Structures	12
Links	12
Table Structure - Standard Network	12
Table Structure - Premium Network	13
Area Type Classification	14
Road_class Classifications	15
Display Characteristics	15
Appendix A: Notes	18
Opening Multiple RouteFinder Networks	18
Maximum Height, Weight, and Width	18

Introduction

Welcome to the product guide for MapInfo RouteFinder. This chapter provides an overview of the product, the documentation, and how to contact us.

Following [Getting Started on page 8](#), the information relating to the product's file sets is given in [Database Description on page 11](#), which will be of particular use if you have the Editable version of MapInfo RouteFinder.

The guide assumes that you are familiar with your MapInfo RouteFinder software. For information about MapInfo RouteFinder, consult the RouteFinder documentation set.

In this chapter:

- ◆ [Overview7](#)
- ◆ [Contacting Technical Support7](#)
- ◆ [Data Vintage7](#)

Overview

MapInfo RouteFinder comprise digital road networks at a nominal 1:10 000 scale, with a link structure. The networks include motorways, principal highways, important regional and local roads, other roads and ferries.

Pitney Bowes Software has enhanced the networks by including the signposted travel speeds, weight limits (where available), and other road and area attributes for each road link. The networks were developed for use with MapInfo RouteFinder software.

Contacting Technical Support

In the unlikely event that you encounter problems working with MapInfo RouteFinder, our technical support specialists can help - refer to [Further Information on page 4](#).

Technical support for RouteFinder includes referrals to documentation, assistance with error messages and suggestions for causes of error messages.

A Technical Support contract can be obtained through your sales representative.

Data Vintage

Pitney Bowes Software Data Products explicitly show the 'vintage' of the source data in unambiguous terms. 'Vintage' refers to the currency of the data as of a specific date and does not correspond exactly to the time of product release, because of data-to-product production time, or reflect the actual ship date.

All product media, product documentation, and product metadata prominently display the data vintage using the following notation:

```
YYYY.MM { (Month Year) }
```

where:

YYYY is the four-digit year

MM is the data vintage's calendar month (01–12)

and optionally:

Month is the three character abbreviation of the month name

Year is the four-digit year

Getting Started

This chapter explains the file names used, and provides you with instructions for installing the data.

In this chapter:

- ♦ [File Names](#)9
- ♦ [Installing RouteFinder Data](#).....10

File Names

MapInfo RouteFinder includes the following file sets:

- **Links:** These Mapinfo format-mappable sets are used for network editing and display.
- Other essential files (.bin, .spd and .ini files): These files are all required for the successful running of the software with a network.

Note In order to use the data correctly, you must have access to all of the files in the file set. All the files for each file set must be located in the same directory.

Links

The Links file sets contain five different file types:

Filename		File Type
Standard Network	Premium Network	
xxx_links.DAT	xxx_links_pro.DAT	Data file
xxx_links.ID	xxx_links_pro.ID	Identification file
xxx_links.IND	xxx_links_pro.IND	Index file
xxx_links.MAP	xxx_links_pro.MAP	Map file
xxx_links.TAB	xxx_links_pro.TAB	Tabular file

In the above table, xxx represents the country / group three-letter code:

Three Letter Code	Country / Group	Three Letter Code	Country / Group
AUT	Austria	ITA	Italy, Vatican City, and San Marino
BEL	Belgium and Luxembourg	NLD	The Netherlands
CHE	Switzerland	NOR	Norway
DEU	Germany	SWE	Sweden
DNK	Denmark	FIN	Finland
FRA	France	GBR	United Kingdom
ESP	Spain, Andorra, and Gibralta	GBR_ITN	ITN network for the United Kingdom
AUS*	Australia	SGP	Singapore
MYS	Malaysia	CHN	China
JPN	Japan	NZL	New Zealand
CAN	Canada	USA*	United States of America

* State networks are available for these countries.

Installing RouteFinder Data

Note Make sure that you choose a disk with enough space.

1. Locate the **install** executable file (install.exe) and double-click it.
2. The MapInfo RouteFinder Data Installer dialog box opens. Click **Next**.
3. Accept the License Agreement by selecting **I accept the terms of the License Agreement** radio button.
4. Click **Next**.
5. Click **Choose** to select a folder where you want to install the RouteFinder data. Also choose where would you like to create product icons by selecting the appropriate radio button. If you do not want to create product icons, select the **Don't create icons** radio button.
6. If you want to create icons for all the users, select the **Create Icons for All Users** check box.
7. Click **Next** to review the disk space availability and other selections.
8. Click **Install**.
9. Click **Done** once the installation process is complete.

Database Description

This chapter describes the spatial referencing, display characteristics, and table structure, of the StreetPro database.

In this chapter:

- ◆ [Spatial Referencing](#)12
- ◆ [Display Characteristics and Table Structures](#)12

Spatial Referencing

The database for MapInfo RouteFinder uses, by default, the projection and coordinates given below:

Coordinate System	Longitude/Latitude(WGS84) Longitude/Latitude(GDA94) (Australia only)
Coordinate Units	Decimal Degrees
Projection	Longitude/Latitude

Display Characteristics and Table Structures

Links

The Links table contains road and ferry links.

Table Structure - Standard Network

Field	Description	Type (Width)	Indexed
Street1	Official Street name	Char(*)	No
Street2	Alternate Street name \ Official Street name in Local Language	Char(*)	No
Street3^	Alternate Street name 2 \ Official Street name in second Local Language	Char(*)	No
Street4^	Alternate Street name 3 \ Official Street name in third Local Language	Char(*)	No
Attribute	Routefinder Road Class value	Small Integer	No
Road_class	Road classification code (please refer to Road_class Specification table below)	Char(2)	No
Area_type	Code representing the Area type	Small Integer	No
FeatureID	Unique Feature Identifier	Char(14)	Yes
Speed	Speed limit for the segment	Integer	No
Start_Z	Value indicating the z-level at the start of the segment	Small Integer	No
End_Z	Value indicating the z-level at the end of the segment	Small Integer	No
Max_Height	Maximum Vehicle Height allowed along the segment	Small Integer	No

Field	Description	Type (Width)	Indexed
Max_Width	Maximum Vehicle Width allowed along the segment	Small Integer	No
Max_Weight	Maximum Vehicle Weight allowed along the segment	Small Integer	No

^ Country specific

Table Structure - Premium Network

Field	Description	Type (Width)	Indexed
Street1	Official Street name	Char(*)	No
Street2	Alternate Street name \ Official Street name in Local Language	Char(*)	No
Street3^	Alternate Street name 2 \ Official Street name in second Local Language	Char(*)	No
Street4^	Alternate Street name 3 \ Official Street name in third Local Language	Char(*)	No
Attribute	Routefinder Road Class value	Small Integer	No
Road_class	Road classification code (please refer to Road_class Specification table below)	Char(2)	No
Area_type	Code representing the Area type	Small Integer	No
FeatureID	Unique Feature Identifier	Char(14)	Yes
Speed	Speed limit for the segment	Integer	No
Speed_AMPeak*	Average speed along segment during AM Peak times	Integer	No
Speed_PMPeak*	Average speed along segment during PM Peak times	Integer	No
Speed_OFT*	Speed value during the Office of Fair Trading preferred time	Integer	No
Speed_InterPeak*	Time between end of AM peak and beginning of PM peak	Integer	No
Speed_NightTime*	Average speed for Night	Integer	No
Start_Z	Value indicating the z-level at the start of the segment	Small Integer	No

Display Characteristics and Table Structures

Field	Description	Type (Width)	Indexed
End_Z	Value indicating the z-level at the end of the segment	Small Integer	No
Max_Height	Maximum Vehicle Height allowed along the segment	Small Integer	No
Max_Width	Maximum Vehicle Width allowed along the segment	Small Integer	No
Max_Weight	Maximum Vehicle Weight allowed along the segment	Small Integer	No

^ Country specific

* Speed Profile data, all fields may not be available

Note The Table Structure may vary from country to country due to extra reference fields but all of the key fields listed above will be present.

The value quoted in the Speed column is derived differently depending on the Country and the source data provider. For any country built from the TomTom source data, the Speed value is the same as the value quoted in the source data. For New Zealand and Japan, the Speed value is equal to the sign-posted speed limit along the segment. For Australia, the Speed value is a combination of sign-posted speed limits and modelled speeds (based on data captured during field verification). For other countries, the Speed value is a modelled speed.

Area Type Classification

There are different Area_Type classifications used globally and the table below details the Area Type values that are available within the networks and the classifications they represent.













Code	Description
TomTom Source Data	
0	Area classed as Rural or
1	Area classed as Urban
Partner Source Data	
1	Area classed as Dense Urban \ Central Business District
2	Area classed as Urban
3	Area classed as Rural Urban
4	Area classed as Rural

Road_class Classifications

Similar to the Area_Type, there is different Road_class classifications dependant on the source data used to build the network. The tables below details the Road_class codes, the Features that the codes represent, and the graphic object details.













Display Characteristics





The first table is for networks built using the TomTom source data.

Feature	Road Classification	Graphic Object Details	
Motorway	M (non-toll), N (toll)		Red, medium polyline Pen (3,2,16711680)
Major Road	I (non-toll), G (toll)		Red, medium polyline Pen (3,2,16711680)
Other Major Road	P (non-toll), Q (toll)		Red polyline Pen (2,2,16711680)
Secondary Road	S (non-toll), T (toll)		Dark yellow polyline Pen (2,2,15790080)
Local Connecting Road	C (non-toll), F (toll)		Saddle polyline Pen(30,130,14401683)
Local (Important) Road	L (non-toll), W (toll)		Saddle polyline Pen(30,130,14401683)
Local Road	D (non-toll), E (toll)		Saddle polyline Pen(30,130,14401683)
Local (Minor) Road	R (non-toll), A (toll)		Saddle polyline Pen(30,130,14401683)
Other Road	U (non-toll), V (toll)		Saddle polyline Pen(30,130,14401683)
Limited Access/Private Road	Z		Pen (1,5,16744448)
Ferry	H		Blue, dashed polyline Pen (1,9,255)
Pedestrian	Z		Pen (1,5,16744448)

Display Characteristics and Table Structures

The second table is for networks built using source data from Data Partners.

Feature	Road Classification	Graphic Object Details	
Motorway	A (non-toll), B (toll)	Standard 	Pen (40,130,13777980) Pen (1,68,1377980) (Tunnel)
		Tunnel 	
Highway	C (non-toll), D (toll)	Standard 	Pen (40,130,7116418) Pen (1,68,7116418) (Tunnel)
		Tunnel 	
Main Road	G (non-toll), H (toll)	Standard 	Pen (30,130,8762781) Pen (1,68,8762781) (Tunnel)
		Tunnel 	
Connector Road	I (non-toll), J (toll)	Standard 	Pen (30,130,14401683) Pen (1,68,15518117) (Tunnel)
		Tunnel 	
Local Road	K (non-toll), L (toll)	Standard 	Pen (1,2,14401683) Pen (1,68,15518117) (Tunnel)
		Tunnel 	
Minor Road	M	Standard 	Pen (1,5,16744448)
Four Wheel Drive Track	N	Standard 	Pen (1,12,14401683)

Feature	Road Classification	Graphic Object Details	
Limited Access	E	Standard 	Pen (1,2,14401683)
Restricted Access	PR	Standard 	Pen (1,2,14401683)
Intersection Construction Line	X	Standard	Invisible unless selected – Pen (1,1,0)
Passenger Ferry	Q	Standard	Pen (1,9,255)
Vehicle Ferry	F	Standard 	
Pedestrian	P	Standard 	Pen (1,3,14401683)



Notes

Opening Multiple RouteFinder Networks

It is not possible to open more than one MapInfo RouteFinder network at a time.

Maximum Height, Weight, and Width

Maximum limits for vehicle height, weight, and width can be specified for each link using the relevant fields within the network. A value of zero in these fields equates to No Limit specified. The maximum values that can be set are 25m for both Height and Width, and 100 tonnes for Weight. The limits for the Height, Weight, and Width can be set to 0.1 of the respective unit.

The values displayed in these fields will be the limit multiplied by 10. For example, if the segment has a Height limit of 3.2m, the value displayed in the Height_limit field will be 32.